



Our Product Range



<p>Submersible Sewage Pump B Series</p> 	<p>Operation Data</p>	<p>: Max. 70 m³/min : Max. 60 m : 0°C to 40°C : 0.75kW to 90kW</p>
	<p>Application</p>	<ul style="list-style-type: none"> - Sewage Treatment Plant (STP) - Flood Control - Transfer Solid Matter
<p>Submersible Wastewater Pump SF Series</p> 	<p>Operation Data</p>	<p>: Max. 1.9 m³/min : Max. 45m : 0°C to 40°C : 0.75kW to 11kW</p>
	<p>Application</p>	<ul style="list-style-type: none"> - Draining Treated Water - Pumping Rainwater & Springwater
<p>Submersible Drainage Pump KTV Series</p> 	<p>Operation Data</p>	<p>: Max. 0.9 m³/min : Max. 35m : 0°C to 40°C : 0.75kW to 5.5kW</p>
	<p>Application</p>	<ul style="list-style-type: none"> - Draining Sand-carrying Water - Deep well Pre-Dewatering
<p>Submersible Resin Pump PU Series</p> 	<p>Operation Data</p>	<p>: Max. 0.8 m³/min : Max. 25m : 0°C to 40°C : 0.15kW to 3.7kW</p>
	<p>Application</p>	<ul style="list-style-type: none"> - Transferring Wastewater - Draining Sewage - Pumping Rainwater & Springwater

Our Product Range



<p>Submersible Wastewater Pump NH Series</p> 	<p>Operation Data</p>	<p>: Max. 2.2 m³/min : Max. 45m : 0°C to 40°C : 1.5kW to 7.5kW</p>
	<p>Application</p>	<ul style="list-style-type: none"> - Draining Wastewater - Drainage - High-head Pumping Wastewater contain solid matters
<p>Variable Speed Controlled Booster Pump System IQ-Series</p> 	<p>Operation Data</p>	<p>: Max.720 m³/hr : Max. 220 m : 2 to 6 units pump in parallel operation : 0°C to 70°C : 0.75kW to 22kW</p>
	<p>Application</p>	<ul style="list-style-type: none"> - Water Procurement - Water Treatment - Water Supply - Water Raising