

# SPRINKLER SYSTEM ACCESSORIES



## Single Low Pressure Control

- ◆ Pressure range : 1 to 10 bar
- ◆ Differential pressure 1 to 3 bar
- ◆ Single-Pole Double Throw (SPDT) contacts
- ◆ Adjustment of range and differential can be done by turning the hexagonal screw

### Application

Pressure sensing of sprinkler system to provide automatic starting of sprinkler system pumps.

Code No.	SPR266-P77-10-CH
	SPR266-CU-STD-CH



## Flowswitch

Single-Pole Double Throw (SPDT) flow switch. To provide an electrical alarm signal when a flow in the sprinkler system occurs. Operation of the flowswitch may be checked by opening the inspection test valve. Adjustable flow paddle, suitable for 1" to 6" pipe. 1" NPT thread connection for installation into screwed tee fitting.

- ◆ Mounting: Vertical or horizontal

Code No.	SPR265-F61KB-CH
----------	-----------------



## Bourdon Tube Pressure Gauge

- ◆ For gaseous and liquid media that are not highly viscous or crystallising and will not attack copper alloy parts
- ◆ Pneumatics
- ◆ Scale ranges 0 to 20 bar
- ◆ Nominal size 100 mm
- ◆ Process Connection : lower mount (LM) G 1/2B

Code No.	SPR187-XX-300-XX
----------	------------------



## Sight Glass Flow Connection

This is used for visual checking of water flow and water filling of pipe at test point. To be installed in main drain lines inspection for test pipes.

- ◆ Working pressure : 10 bar
- ◆ Test pressure : 15 bar
- ◆ Connection : 1" BSP Thread

Code No.	SPR004-GM-025-VL
----------	------------------



## Recessed Sprinkler Rosette

Suitable for 1/2" sprinkler Adjustable rosettes Stainless Steel available

Code No.	Material
SPR178-MS-015-CH	M.S Chrome
SPR178-MS-015-WH	M.S Epoxy White



## Sprinkler Wrench

Used for installation of upright and pendant sprinklers

Code No.	Material
SPR177-MS-STD-BK	M.S. Epoxy Black



## Plain Sprinkler Rosette

Suitable for 1/2" sprinkler Adjustable rosettes Stainless Steel available

Code No.	Material
SPR173-MS-015-CH	M.S Chrome
SPR173-MS-015-WH	M.S Epoxy White



## Sprinkler Guard

To be used for areas where the sprinkler may be susceptible to be accidentally struck

Code No.	Material
SPR179-MS-015-CH	M.S Chrome