

Chrome Finished Jet & Spray Nozzle

SRI hose reel nozzles are designed, tested and approved to meet European Standard EN671-1 and Australian

Standard AS 1221.

Nylon and ABS material complies to ageing test in accordance to ISO4892-2.2.

Throw range position at 0.6M 30± inclination, in accordance to EN671-1 Clause 10.4

Flowrate meets the equivalent nozzle diameter of 6mm in accordance to EN671-1.



HRS050-GM-020-CH
HRS050-GM-025-CH

HRS039-GM-020-CH
HRS039-GM-025-CH
HRS039-GM-020-NA
HRS039-GM-025-NA

Description

Code No.	Setting	Material	Finishing	Inlet Size	Flowrate @ 30Psi (2.0 BAR)	Throwrange @ 30Psi (2.0 BAR)
HRS050-GM-020-CH	Jet	Brass	Chrome	3/4" (19 mm)	27L/MIN	11.0M
HRS050-GM-025-CH	Jet	Brass	Chrome	1" (25 mm)	32L/MIN	11.0M
HRS039-GM-020-CH	Jet / Spray	Brass	Chrome	3/4" (19 mm)	27L / MIN (JET)	11.0M
HRS039-GM-025-CH	Jet / Spray	Brass	Chrome	1" (25 mm)	32L / MIN (JET)	11.0M
HRS039-GM-020-NA	Jet / Spray	Brass	Chrome	3/4" (19 mm)	27L / MIN (JET)	11.0M
HRS039-GM-025-NA	Jet / Spray	Brass	Chrome	1" (25 mm)	32L / MIN (JET)	11.0M