

LOVE EACH OTHER



Stainless Steel Vertical Multistage Pump

LVR / LVS



APPLICATIONS:

- ◆ General Industry
- ◆ Building Services
- ◆ Chemical Industry
- ◆ Heat and Steam Generation
- ◆ Cooling Water Supply
- ◆ Irrigation
- ◆ Water Treatment
- ◆ Fire Fighting and Sprinkler Systems
- ◆ Pressure Boosting
- ◆ MVAC



SPAN
Suruhanjaya Perkhidmatan Air Negara



TYPE OF STRUCTURES



LVR



LVS

Share, Synchronize, Implement, Improve

STAINLESS STEEL VERTICAL MULTISTAGE PUMP

LVR / LVS



Pump - Technical Data

Max. Flow	240 m ³ /h
Max. Head	323 m
Liquid Temperature	-20 °c ~ +120 °c
Max. Working Pressure	33 Bar
Power Range	0.37 - 110 kW
Connection	DN25 - 150

Motor

Standard Efficiency
Insulation Class
Protection Class
Standard Voltage

IE2 Motor (IE3 is available on request)
F
IP55
50Hz

Pump - Material


	LVR	LVS
Casing	Stainless Steel (AISI304)	(AISI304)
Impeller	Stainless Steel (AISI304)	(AISI304)
Pump Shaft	Stainless Steel (AISI316)	(AISI316)
Base	Cast Iron (HT200)	Aluminum Alloy (ADC12)



LVR

LVS

Performance Chart - LVR, LVS



LEO PUMP ENGINEERING (MALAYSIA) SDN. BHD. (1414432-U)



No. 21 & 23, Jalan USJ 1/31, 47600 Subang Jaya, Selangor Darul Ehsan, Malaysia

Tel : 603-8024 8213 Fax : 603-8024 8215 E-mail : enquiry@leogroup.com.my www.leogroup.com.my

LPEM-LVSLVR-1221-03

All specifications are subject to change prior notice for product improvement. Picture and images used are for illustrative purposes only and the color printed may different from the actual product.