

## WET & DRY RISER EQUIPMENT

### Ratio Type Landing Valve to BS5041



Code No.	Inlet Size	Outlet Size	Flowrate
WRS124-LG-3X1-RD			
WRS124-LG-2X1-RD	Male BSP Thread 80 mm	BS 336 Female	min 510 l/min
WRS124-LG-3X2-RD			

### 2 Way & 4 Way Breeching Inlet

- ◆ Body : Ductile Iron
- ◆ Inlet : BS Instantaneous Male Copper Alloy to BS 1982
- ◆ Outlet : 2 Way Breeching Inlet Flanged PN16  
: 4 Way Breeching Inlet Flanged PN16  
: 2 Way Breeching Inlet Flanged 3" ANSI
- ◆ Working Pressure : 10 bar
- ◆ Testing Pressure : 20 bar



**DRS095-DI-BSPN16**



**WRS115-DI-BSPN16**









**DRS130-GM-STN-NA**



**WRS130-GM-90D-NA**



**WRS104-GM-020-NA**

Code No.	Description	Inlet Size	Outlet Size	Body Material
DRS095-DI-BSPN16	2 way breeching inlet	BS 336 Male	Table E/PN16	Ductile Iron 
WRS115-DI-BSPN16	4 way breeching Inlet	BS 336 Male	Table E/PN16	Ductile Iron 
DRS095-DI-2WY-RD	2 way breeching inlet	BS 336 Male	Table E/PN16	Ductile Iron 
WRS115-DI-4WY-RD	4 way breeching Inlet	BS 336 Male	Table E/PN16	Ductile Iron 
DRS095-DI-002-RD	2 way breeching inlet	BS 336 Male	Table E/PN16	Ductile Iron 
WRS115-DI-004-RD	4 way breeching Inlet	BS 336 Male	Table E/PN16	Ductile Iron 

Optional : ANSI Flange available upon request

### German Breeching Inlet

Code No.	Description	Outlet Size	Inlet Size
DRS130-GM-STN-NA	2 way breeching inlet	Female BSP Thread 80 mm	Storz B75 (89 mm)

### German Landing Valve

Code No.	Inlet Size	Outlet Size
WRS130-GM-90D-NA	Male BSP Thread 50 mm	Storz C52 (66 mm)
WRS130-LA-90D-NA	Male BSP Thread 50 mm	Storz C52 (66 mm)

### Air Release Valve

Code No.	Inlet Connection
WRS104-GM-020-NA	20 mm BSP
WRS104-GM-025-NA	25 mm BSP