



## **STRENGTH**

Compressive Strength 45MPa

# LIGHTER

Ease of Laying

### **GENERAL INFORMATION**

The thickness and design of a concrete segmental pavement is subject to:

- · Traffic volume estimation
- · Soil & subgrade investigation
- · Surface design
- · Basecourse thickness design
- · Design considerations for low-strength subgrades or irregular-shaped areas

#### **COMPRESSIVE STRENGTH**

Z Series (60mm), 45MPa

IP Rating: IP65

MS1380: 1995 (SPECIFICATION FOR PRECAST CONCRETE PAVING BLOCK)

(MA 20 Requirement : Australian Standard)

BS6717: 1993 (SPECIFICATION FOR PRECAST CONCRETE PAVING BLOCK)

#### **TOLERANCE**

Thickness of any paver may be ± 3mm

## **HEAVY-DUTY APPLICATIONS**

- Residential & Commercial Driveway
- Road Junctions & Roundabouts
- Warehouses
- · Housing Estate Internal Roads
- Carparks
- Drop-off Area

#### **EFFLORESCENCE**

This superficial phenomenon is commonly found in most concrete-based or cementitious products. However, this efflorescence effect will disappear over time (weathering) whereby rain usually washes the efflorescence away in about six months to a year and in the worst-case scenario could take up to two years.

#### **AESTHETICS**

Variety of colours leads to interesting designs

## **ABSOLUTE DURABILITY**

- Minimal maintenance
- Hard wearing surface
- High skid resistance

## **IMMEDIATE USE ADVANTAGE**

- Can be opened to traffic immediately upon completion of paved area

## **EASY ACCESS TO UNDERGROUND UTILITY SERVICES**

- Can be lifted and relaid easily and rapidly without unsightly scars

## **VERSATILE COLOUR CODING POSSIBILITIES**

- Different permanent colours can be used to delineate separate areas
- Indicate parking bays
- Permanent road marking; location of underground services

#### EASE OF LAYING

 Inaccessible areas with slopes and gradients can be paved without use of heavy equipment

#### **FUNGAL RESISTANCE**

- Able to reduce the formation of fungus/algae on the paver surface

## **Antique Colours**



Various shades of Antique.

## **Standard Colours**




## **Premium Colours**



Colours can be custom-made to suit your design requirements or preferences.

Note Finished product colour may vary, subject to the colour of sand, cement and colour pigments used at the time of production.

#### TYPICAL PAVEMENT CROSS-SECTION



# SUNWAY BUILDING MATERIALS

# SUNWAY PAVING SOLUTIONS SDN BHD

# CENTRAL SALES & MARKETING OFFICE:

#3.2, Level 3, Menara Sunway, Jalan Lagoon Timur, Bandar Sunway, 47500, Selangor Darul Ehsan, Malaysia. Tel: (+603) 5639 8282 Fax: (+603) 5639 9600, 5639 9606

Factory: Batang Kali

**BANDAR SUNWAY** 

Lot 10071, Mukim Batang Kali, 44300 Daerah Ulu Selangor, Selangor Darul Ehsan, Malaysia,

Tel: (+603) 6057 2407 Fax: (+603) 6057 2423

#### Northern Region Sales & Marketing Office/ Factory: Nibong Tebal

Lot 2788, 2796, 2797, Kawasan Perindustrian Bukit Panchor, Mukim 7, Nibong Tebal, Seberang Perai Selatan, 14300 Pulau Pinang, Malaysia.

Tel: (+604) 593 8697/8 Fax: (+604) 593 8695

#### East Coast Region Sales & Marketing Office/Factory: Marang

Lot PT 16574, Kawasan Perindustrian, Bukit Kor, 21600, Mukim Rusila, Marang, Terengganu Darul Iman. Tel: (+609) 617 3925 Fax: (+609) 617 3923

E-mail: spssales@sunway.com.my Website: www.sunwaypavingsolutions.com Facebook: www.facebook.com/sunwaypavingsolutions

## Southern Region Sales & Marketing Office/ Factory: Senai

PLO 6, Jalan Lapangan Terbang, Fasa 1, Kawasan Perindustrian Senai, 81400 Senai, Johor Darul Takzim, Malaysia. Tel: (+607) 599 5553 Fax: (+607) 599 3827









Information contained within this figer is correct at the time of printing (May 2015). Colours shown are reproduced as close to the actual colours as printing technology allows. Measurements are approximate. While every reasonable care has been taken in preparing this flyer, we cannot be held responsible for any inaccuracy. All admitstations are affects impression sonly. This flyer does not from any part of the critical.